



PRODUCT DESCRIPTION

BD Butyl Tape FR is a butyl rubber adhesive tape with a polyester fabric backing.

USES

BD Butyl Tape FR is designed to be used in conjunction with Bridge Preservation™ spray applied waterproofing products to provide reinforcement as required.

ADVANTAGES

- Excellent adhesion
- Aggressive grip
- Easily applied with no special equipment
- Compatible with all Bridge Preservation™ spray applied waterproofing products
- Easy and fast application
- Fabric backing allows for top coating

PHYSICAL PROPERTIES

Adhesive		Modified Butyl
Backing		Polyester
Bonding Time		Immediate
Tensile Strength		790 psi, average
Peel Strength		17 lbs./linear inch
Thickness	ASTM D1000	25 mils
Elongation	ASTM D1000	560%, average

PACKAGING

Tape Width	Rolls*/Case	Linear Feet/Case
4"	6	300
6"	4	200

**All rolls are 50 feet in length. Other roll widths are available upon request.*

SURFACE PREPARATION

Provide clean, sound substrate. Remove all grease, scale, dirt, and rust on the steel and/or concrete surfaces to receive tape using abrasive blasting or wire brush. To assure adhesion, the surface must be clean, dry, and free of grease.

APPLICATION

Peel back interleaving and apply adhesive side of the tape to the surface and press down. Ensure that all seams and overlaps are pressed out and adhered. A top coat can be applied immediately after BD Butyl Tape FR is installed.

WARRANTY

Bridge Preservation will refund the price or replace, at its election, product it finds to be defective provided the product has been stored and used properly. Except as expressly stated above, the Company makes no

warranty of merchantability and no warranty of fitness for any particular purpose, nor does it make any warranty, expressed or implied, of any nature whatsoever with respect to the product or its use. In no event shall the company be liable for delay caused by defects, for loss of use, for indirect, special, or consequential damages, or for any charges or expenses of any nature incurred without its written consent.